



Min Flow Rate: 59m ³ /h (260 GPM)		Project: Filtration		 <p>NETAFIM™</p> <p>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED.</p>																
Max Flow Rate: 95m ³ /h (418 GPM)		Subject: HYDROCYCLONES																		
Pressure: 10bar (145 PSI)		SAP Code / Item Description: 71990-000321 / NET. HYDROCYCLONE 4"S VIC+TANK 60L NPT																		
Sheet Size: A4	Scale: 1:10	General Tolerance According to ISO 2768-		Designed By: KEREM K. 06.09.2022																
		LINEAR DIMENSIONS		Checked By: KEREM K. 06.09.2022																
		Permissible deviations in mm for ranges in nominal lengths																		
		<table border="1"> <tr> <td>≥ 0.5</td> <td>> 3</td> <td>> 6</td> <td>> 30</td> <td>> 120</td> <td>> 400</td> <td>> 1000</td> <td>> 2000</td> </tr> <tr> <td>≤ 3</td> <td>≤ 6</td> <td>≤ 30</td> <td>≤ 120</td> <td>≤ 400</td> <td>≤ 1000</td> <td>≤ 2000</td> <td>≤ 4000</td> </tr> </table>		≥ 0.5	> 3	> 6	> 30	> 120	> 400	> 1000	> 2000	≤ 3	≤ 6	≤ 30	≤ 120	≤ 400	≤ 1000	≤ 2000	≤ 4000	Permissible deviations in degrees and minutes for ranges in nominal lengths
≥ 0.5	> 3	> 6	> 30	> 120	> 400	> 1000	> 2000													
≤ 3	≤ 6	≤ 30	≤ 120	≤ 400	≤ 1000	≤ 2000	≤ 4000													
		<table border="1"> <tr> <td>≤ 10</td> <td>> 10</td> <td>> 50</td> <td>> 120</td> <td>> 400</td> </tr> <tr> <td>≤ 5</td> <td>≤ 50</td> <td>≤ 120</td> <td>≤ 400</td> <td></td> </tr> </table>		≤ 10	> 10	> 50	> 120	> 400	≤ 5	≤ 50	≤ 120	≤ 400								
≤ 10	> 10	> 50	> 120	> 400																
≤ 5	≤ 50	≤ 120	≤ 400																	
3-D Proj. 				Sheet: 2 Of: 12 Rev. B																