

Aries™ MWD

Integral non pressure-compensated,
high clogging resistance dripper,
for multi seasonal applications

→ 12200 - 12250 - 16200 - 16250 - 16008 - 22250



High clogging
resistance



Self-cleaning
labyrinth



Wide filtration
area

Benefits & Features

- High clogging resistance Even with poor quality water, with self-cleaning labyrinth that flushes debris, throughout operation.
- Wide filtration area Ensures optimal performance even under harsh water conditions, preventing the entrance of sediments into the drippers.
- TurbuNext™ Labyrinth ensures wide water passages, large deep and wide cross section that improves clogging resistance.

Specifications

- ✓ Maximum system pressure: according to driplines wall thickness.
- ✓ Recommended filtration: depending on dripper flow rate. Filtration method selected based on the kind and concentration of dirt particles contained in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclone shall be installed before the main filter. Where sand/silt/clay solids exceed 100 ppm, pre treatment shall be applied following Netafim expert instructions.
- ✓ TurbuNext™ labyrinth with superior performance.
- ✓ Weldable into medium wall driplines (0.50 , 0.63, 0.80 mm).
- ✓ Injected dripper, very low CV.
- ✓ High UV resistant. Resistant to standard nutrients used in agriculture.
- ✓ Aries™ driplines meet ISO 9261 Standards with Israel Standard Institute (SII)-certified production.

→ DRIPPERS TECHNICAL DATA

12200, 12250, 16200, 16250, 22250 - 0.50, 0.63 mm wall thickness driplines

FLOW RATE* (L/H)	MAXIMUM WORKING PRESSURE (BAR)**	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.50	2.5 / 3.0 / 3.5	0.47 x 0.53 x 65	39	0.173	0.46	130/120
0.80		0.54 x 0.69 x 65	43	0.277	0.46	130/120
1.00		0.60 x 0.74 x 65	49	0.347	0.46	200/80
1.40		0.71 x 0.85 x 65	53	0.485	0.46	200/80
1.90		0.76 x 1.03 x 65	54	0.659	0.46	200/80
2.85		0.90 x 1.20 x 65	54	0.988	0.46	200/80
3.80		0.94 x 1.28 x 33	54	1.316	0.46	200/80
8.00		1.52 x 1.28 x 28	50	2.773	0.46	200/80

*Flow rate at 1.0 bar pressure **According to driplines diameter and wall thicknessess

→ DRIPPERS TECHNICAL DATA

16008 - 0.8 mm wall thickness driplines

FLOW RATE* (L/H)	MAXIMUM WORKING PRESSURE (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.55	3.0	0.47 x 0.53 x 65	39	0.191	0.46	130/120
0.80		0.54 x 0.69 x 65	43	0.277	0.46	130/120
1.00		0.60 x 0.74 x 65	49	0.347	0.46	200/80
1.50		0.71 x 0.85 x 65	53	0.520	0.46	200/80
2.00		0.76 x 1.03 x 65	54	0.693	0.46	200/80
3.00		0.90 x 1.20 x 65	54	1.040	0.46	200/80
4.00		0.94 x 1.28 x 33	54	1.387	0.46	200/80
8.00		1.52 x 1.28 x 28	50	2.773	0.46	200/80

*Flow rate at 1.0 bar pressure

→ DRIPPLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
12200	11.80	0.50	12.80	3.0	3.9	0.40
12250	11.80	0.63	13.06	3.5	4.6	0.40
16200	15.50	0.50	16.50	2.5	3.3	0.35
16250	15.50	0.63	16.76	2.8	3.6	0.35
16008	15.50	0.80	17.10	3.0	3.9	0.35
22250	22.20	0.63	23.56	2.5	3.3	0.06

→ DRIPINES PACKAGE DATA (ON CARTON COIL)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
12200	0.50	0.15 to 0.25	800	17.6	480	384000
		0.30 to 1.00	900	18.8	480	432000
12250	0.63	0.15 to 0.25	700	19.0	480	336000
		0.30 to 1.00	750	19.6	480	360000
16200	0.50	0.15 to 0.25	850	23.1	480	408000
		0.30 to 1.00	900	23.7	480	432000
16250	0.63	0.15 to 0.25	750	25.4	480	360000
		0.30 to 1.00	800	26.3	480	384000
16008	0.80	0.15	450	19.4	480	216000
		0.20 to 1.00	500	21.0	480	240000
22250	0.63	0.15 to 0.25	550	25.7	480	264000
		0.30 to 1.00	600	27.4	480	288000

* Calculated weight average. For further details see "Average Coil Weight Disclaimer".

Drippers flow rate vs. working pressure

In order to calculate the right flow rate of each dripper, under different working pressures, we use the following formula:

$$Q = K * P^x$$

Where:

Q = Dripper flow rate (liters/hour)

K = Constant (each dripper has his singular constant and must be defined by the dripper producer)

P = Real working pressure (meter)

X = Exponent (each dripper has its singular exponent and must be declared and defined by the dripper producer)

*ISO 9261 require from the manufacturer to declare the constant K and dripper exponent

Non-regulated drippers provide flow adequate to the pressure it is exposed to, according to the formula presented above. In order to simplify the calculations and understandings of the linkage between the flow and the pressure, a table with the flow rates at different working pressures is presented here for each of the drippers presented in this document.

Flow rate (l/h) vs. Pressure (bar)

12200, 12250, 16200, 16250, 22250 - 0.50 and 0.63 mm wall thickness dripperlines

FLOW RATE* (L/H)	PRESSURE (BAR)								
	0.2	0.4	0.6	0.8	1.0	1.5	2.0	2.5	3.0
0.50	0.24	0.33	0.39	0.45	0.50	0.60	0.69	0.76	0.83
0.80	0.38	0.52	0.63	0.72	0.80	0.96	1.10	1.22	1.32
1.00	0.48	0.66	0.79	0.90	1.00	1.21	1.38	1.53	1.66
1.40	0.67	0.92	1.11	1.26	1.40	1.69	1.92	2.13	2.32
1.90	0.91	1.25	1.50	1.72	1.90	2.29	2.61	2.90	3.15
2.85	1.36	1.87	2.25	2.57	2.85	3.43	3.92	4.34	4.72
3.80	1.81	2.49	3.00	3.43	3.80	4.57	5.22	5.79	6.29
8.00	3.81	5.25	6.32	7.22	8.00	9.64	11.00	12.19	13.26

*Nominal flow rate at 1.0 bar pressure

Flow rate (l/h) vs. Pressure (bar)

16008 - 0.8 mm wall thickness dripperlines

FLOW RATE* (L/H)	PRESSURE (BAR)								
	0.2	0.4	0.6	0.8	1.0	1.5	2.0	2.5	3.0
0.55	0.26	0.36	0.44	0.50	0.55	0.66	0.76	0.84	0.91
0.80	0.38	0.52	0.63	0.72	0.80	0.96	1.10	1.22	1.32
1.00	0.48	0.66	0.79	0.90	1.00	1.21	1.38	1.53	1.66
1.50	0.72	0.98	1.19	1.35	1.50	1.81	2.06	2.29	2.49
2.00	0.95	1.31	1.58	1.80	2.00	2.41	2.75	3.05	3.31
3.00	1.43	1.97	2.37	2.71	3.00	3.61	4.13	4.57	4.97
4.00	1.91	2.62	3.16	3.61	4.00	4.82	5.50	6.10	6.63
8.00	3.81	5.25	6.32	7.22	8.00	9.64	11.00	12.19	13.26

*Nominal flow rate at 1.0 bar pressure

/ Max. Lateral length

Flow Variation (FV) expresses the flow variation between the dripper "sensing" the highest pressure and the one "sensing" the lowest pressure in an irrigation block (zone).

These drippers will not always be the first and last drippers on the dripline.

$$FV \% = (Q_{\max} - Q_{\min}) / Q_{\max} * 100$$

*International standards define 10% flow variation to be considered as uniform irrigation.

In order to calculate the maximum run lengths that can be planned for specific dripline (considering all the hydraulic factors influencing the flow within the same dripline), we use a calculation software that was developed by Netafim™ based on Darcy-Waisbach formulas + years of design experience and cooperation with academic institutes.

All the tables presented in this document are for initial reference only; the exact run length of the driplines is obtained from design software that considers various hydraulic factors in the entire system.

There might be small variance between the different software's in the market due to the calculation method and assumptions each software is using. For an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

Non-regulated drippers of Netafim™ will provide different flow according to the real working pressure, therefore, the influencing factors will be: the pressure that each dripper in the dripline is exposed to, and the allowed flow variation the dripline is designed to, which in most cases is defined as 10% difference in flow, according to the international standards, and / or any other limitation that the customer / planner will prefer to design while considering the crop needs and area topography.

The following tables are only displayed at one inlet pressure for each dripline, since in non-regulated drippers the flow varies according to the pressure. There might be differences in run lengths with different inlet pressures; however for an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 0.50 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	72	90	103	113	119	125	130	133	136	
	1%	81	106	126	143	158	170	181	191	199	
FLAT TERRAIN	0	91	124	153	180	205	228	250	272	292	
	-1%	98	138	175	210	242	274	305	335	364	
DOWNHILL	-2%	105	150	192	232	271	308	344	379	413	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 0.80 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	69	86	99	109	116	122	126	131	134	
	1%	77	101	120	137	151	162	174	184	192	
FLAT TERRAIN	0	85	116	144	169	193	214	235	255	274	
	-1%	92	129	163	195	226	255	283	311	338	
DOWNHILL	-2%	98	139	178	216	251	286	319	352	383	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 1.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	51	66	78	89	96	103	109	114	119	
	1%	55	73	89	103	114	125	134	143	151	
FLAT TERRAIN	0	59	80	100	118	134	149	164	178	191	
	-1%	62	86	109	130	151	170	190	208	226	
DOWNHILL	-2%	65	93	119	144	169	193	218	241	265	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 1.40 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	42	56	66	76	83	90	95	101	105	
	1%	45	60	73	85	95	105	113	121	128	
FLAT TERRAIN	0	47	65	81	95	109	120	132	143	154	
	-1%	49	68	86	103	119	134	149	163	177	
DOWNHILL	-2%	51	73	93	112	131	148	166	185	202	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 1.90 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	36	47	56	65	72	78	84	89	93	
	1%	37	50	61	71	80	88	96	103	110	
FLAT TERRAIN	0	39	53	66	78	89	99	109	119	127	
	-1%	40	56	70	84	96	108	120	131	142	
DOWNHILL	-2%	41	58	74	89	104	118	131	145	158	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 2.85 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	28	38	46	53	58	64	69	73	77	
	1%	29	39	48	57	64	70	76	82	87	
FLAT TERRAIN	0	30	41	51	61	68	76	84	91	98	
	-1%	30	42	53	63	73	82	90	99	107	
DOWNHILL	-2%	31	44	56	67	77	88	98	107	117	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 3.80 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	24	32	38	45	50	55	59	64	68	
	1%	24	33	40	48	53	60	65	70	75	
FLAT TERRAIN	0	25	34	42	50	57	64	70	77	82	
	-1%	25	35	44	52	60	67	74	81	88	
DOWNHILL	-2%	26	36	46	55	63	71	79	87	94	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 12200/12250 • ID 11.8 mm • Kd 0.40 • Flow rate 8.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	15	20	24	29	32	36	38	41	44	
	1%	15	20	25	30	34	37	41	44	47	
FLAT TERRAIN	0	15	21	26	31	35	39	42	47	50	
	-1%	15	21	26	32	36	41	45	49	53	
DOWNHILL	-2%	16	22	27	33	37	42	46	50	55	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 0.50 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	98	116	128	135	139	143	145	147	148	
	1%	118	152	176	196	212	225	235	244	251	
FLAT TERRAIN	0	141	194	241	284	324	361	397	430	463	
	-1%	159	227	291	352	410	466	521	574	627	
DOWNHILL	-2%	173	252	326	398	256	216	200	193	188	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 0.80 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	80	99	112	121	127	132	136	140	142	
	1%	91	119	142	161	176	189	200	210	218	
FLAT TERRAIN	0	104	143	178	210	239	267	294	319	343	
	-1%	114	162	206	249		328	366	402	438	
DOWNHILL	-2%	122	176	228	277	325	371	230	252	243	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 1.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	72	90	103	113	120	126	130	134	137	
	1%	80	106	127	144	159	172	182	193	201	
FLAT TERRAIN	0	90	124	154	182	207	231	254	275	297	
	-1%	97	138	176	211	245	278	310	340	370	
DOWNHILL	-2%	104	149	192	234	274	312	350	385	233	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 1.40 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	60	77	90	100	108	114	120	124	128	
	1%	66	88	106	122	135	147	158	167	176	
FLAT TERRAIN	0	72	100	124	147	167	186	205	222	239	
	-1%	77	109	138	166	193	218	242	266	289	
DOWNHILL	-2%	82	117	150	182	212	242	270	299	326	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 1.90 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	51	67	78	89	96	103	109	113	118	
	1%	55	74	90	104	116	126	136	145	153	
FLAT TERRAIN	0	59	82	102	120	137	153	169	183	197	
	-1%	63	88	112	134	155	175	194	213	232	
DOWNHILL	-2%	66	94	120	145	169	192	214	237	258	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 2.85 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	41	54	64	74	81	88	93	98	103	
	1%	43	58	71	83	93	102	110	118	126	
FLAT TERRAIN	0	45	63	78	93	106	118	130	141	152	
	-1%	48	67	84	101	116	132	146	160	174	
DOWNHILL	-2%	49	70	90	108	125	142	158	175	190	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 3.80 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	34	46	56	64	71	77	82	87	92	
	1%	36	49	60	70	79	87	94	102	108	
FLAT TERRAIN	0	38	52	65	77	88	98	108	118	126	
	-1%	39	55	69	83	95	108	119	131	142	
DOWNHILL	-2%	40	57	73	88	102	116	129	141	154	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16200/16250 • ID 15.5 mm • Kd 0.35 • Flow rate 8.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	2%	22	30	36	43	48	53	57	61	65
	1%	1%	23	31	38	45	51	57	62	67	72
FLAT TERRAIN	0	0	23	32	40	48	55	61	67	73	79
	-1%	-1%	24	33	42	50	58	65	72	78	85
DOWNHILL	-2%	-2%	24	34	44	52	61	68	76	83	90

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 0.55 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	2%	94	113	124	132	137	141	144	146	147
	1%	1%	112	144	169	189	204	217	228	237	245
FLAT TERRAIN	0	0	132	182	226	267	304	339	372	404	435
	-1%	-1%	148	211	270	327	380	433	483	533	581
DOWNHILL	-2%	-2%	161	233	303	369	239	251	210	198	192

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 0.80 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	2%	80	99	112	121	127	132	136	140	142
	1%	1%	91	119	142	161	176	189	200	210	218
FLAT TERRAIN	0	0	104	143	178	210	239	267	294	319	343
	-1%	-1%	114	162	206	249	289	328	366	402	438
DOWNHILL	-2%	-2%	122	176	228	277	325	371	230	252	243

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 1.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	2%	72	90	103	113	120	126	130	134	137
	1%	1%	80	106	127	144	159	172	182	193	201
FLAT TERRAIN	0	0	90	124	154	182	207	231	254	275	297
	-1%	-1%	97	138	176	211	245	278	310	340	370
DOWNHILL	-2%	-2%	104	149	192	234	274	312	350	385	233

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 1.50 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	2%	58	75	88	98	106	112	118	122	126
	1%	1%	63	85	102	118	131	142	153	162	171
FLAT TERRAIN	0	0	69	95	118	140	160	179	196	212	229
	-1%	-1%	74	104	132	158	183	207	230	253	275
DOWNHILL	-2%	-2%	78	111	142	173	202	230	257	283	309

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 2.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	50	65	77	87	94	101	106	112	116	
	1%	53	72	87	101	112	123	133	141	150	
FLAT TERRAIN	0	57	79	98	117	133	148	163	177	191	
	-1%	60	85	108	129	149	169	187	206	223	
DOWNHILL	-2%	63	90	116	140	163	185	206	228	248	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 3.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	39	52	63	72	79	85	91	96	101	
	1%	42	56	69	81	90	99	107	115	122	
FLAT TERRAIN	0	44	61	76	90	103	114	126	137	147	
	-1%	46	65	82	98	113	127	141	154	167	
DOWNHILL	-2%	48	68	86	104	121	137	153	168	183	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 4.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	33	45	54	62	69	75	80	86	90	
	1%	35	47	58	68	77	85	92	99	105	
FLAT TERRAIN	0	36	50	63	75	85	95	105	113	122	
	-1%	38	53	67	80	92	104	115	126	137	
DOWNHILL	-2%	39	55	70	85	98	111	124	136	148	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 16008 • ID 15.5 mm • Kd 0.35 • Flow rate 8.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	22	30	36	43	48	53	57	61	65	
	1%	23	31	38	45	51	57	62	67	72	
FLAT TERRAIN	0	23	32	40	48	55	61	67	73	79	
	-1%	24	33	42	50	58	65	72	78	85	
DOWNHILL	-2%	24	34	44	52	61	68	76	83	90	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 0.50 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	136	145	148	150	151	153	153	153	154	
	1%	203	235	255	268	277	283	287	291	294	
FLAT TERRAIN	0	301	399	485	564	636	704	769	831	890	
	-1%	377	526	665	795	505	449	408	390	380	
DOWNHILL	-2%	237	198	185	181	178	177	176	176	175	

Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 0.80 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	128	141	148	152	154	156	158	158	159	
	1%	171	206	230	248	261	271	278	284	291	
FLAT TERRAIN	0	227	301	366	425	480	531	580	627	671	
	-1%	277	392	503	614	723	834	945	431	379	
DOWNHILL	-2%	333	496	177	167	162	160	158	157	156	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 1.00 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	120	135	143	148	152	154	155	157	158	
	1%	154	188	213	232	245	257	266	273	279	
FLAT TERRAIN	0	196	260	317	368	416	460	503	543	582	
	-1%	234	328	419	508	596	683	771	860	949	
DOWNHILL	-2%	275	404	208	177	167	163	161	159	158	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 1.40 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	107	124	134	141	145	148	150	153	154	
	1%	131	162	186	205	220	232	242	252	259	
FLAT TERRAIN	0	158	210	256	297	335	372	406	438	470	
	-1%	182	254	321	387	451	515	578	640	703	
DOWNHILL	-2%	208	301	394	488	190	175	169	165	162	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 1.90 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	94	112	124	132	137	141	146	148	150	
	1%	111	140	162	180	196	208	219	230	237	
FLAT TERRAIN	0	130	173	210	245	276	306	334	361	386	
	-1%	146	202	254	304	353	400	448	495	541	
DOWNHILL	-2%	163	233	302	370	439	509	190	178	172	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 2.85 l/h • Inlet pressure 1.5 Bar

		DISTANCE BETWEEN DRIPPERS (METER)									
		SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	78	96	108	117	125	130	134	139	141	
	1%	89	113	133	150	164	176	187	197	206	
FLAT TERRAIN	0	100	133	162	189	214	236	258	279	299	
	-1%	109	150	188	224	258	292	325	357	389	
DOWNHILL	-2%	120	169	216	262	308	354	399	446	492	

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 3.80 l/h • Inlet pressure 1.5 Bar

	DISTANCE BETWEEN DRIPPERS (METER)									
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	68	84	97	106	114	120	125	130	133
	1%	76	97	115	130	143	155	165	175	183
FLAT TERRAIN	0	83	111	135	157	178	197	215	232	249
	-1%	90	122	152	181	208	235	261	286	311
DOWNHILL	-2%	97	135	172	207	242	277	311	346	380

Max. lateral length (meters) at different slopes - 10% flow variation

Aries™ MWD • 22200/22250 • ID 22.2 mm • Kd 0.06 • Flow rate 8.00 l/h • Inlet pressure 1.5 Bar

	DISTANCE BETWEEN DRIPPERS (METER)									
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
UPHILL	2%	45	57	67	75	82	88	94	98	102
	1%	48	62	74	85	95	104	111	119	125
FLAT TERRAIN	0	51	68	82	96	108	120	131	142	152
	-1%	53	72	89	105	120	134	148	161	174
DOWNHILL	-2%	56	76	95	113	129	146	161	176	191