





MTL SNG 480306 S			V. M	EJAI	rim	
SKU No.				PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		
Maximum Flow Rate: 1122 GPM			Y REPRODUCTION IN PART DLE WITHOUT THE WRITTEN DF NETAFIM IS PROHIBITED			
Recommended Flow Rate: 616 GPM			Designed By			
Inlet Pressure:	115 PSI		Drawn By	KEREM	25/12/2019	
Sheet Size:	Scale:		Checked By			
A4	1:30	TO HIGH PRESSURE TO LOW PRESSURE	QA	Of		
		D.P / D.P	Sheet: 2	^{Of:} 3	Rev	

ITEM NO.	SAP Description	SAP Cat. No.	QTY.
1	METAL SNG.CHA.PLUS 48''*4'' VIC PN08 LONG	71910-001626	3
2	METAL MAN 6"*2 OUT*4" VIC F/48" TANK	71910-001691	2
3	METAL MAN 6"*1 OUT*4" VIC F/48" TANK	71910-001690	2
4	METAL BF MAN 4"*2 OUT*3" VIC F/48" TANK	71910-001712	1
5	METAL BF MAN 4"*1 OUT*3" VIC F/48" TANK	71910-001703	1
6	MET CUP 6"VIC W/2 OUT 2"NPT +1 OUT 1"NPT	71910-001802	2
7	METAL CUP 4" VIC	71910-001792	1
8	NET METAL B.F VALVE 4X3 STRAIGHT VIC	71600-006660	3
9	VICTAULIC COUPLING 3" ONE BOLT	71910-002501	3
10	VICTAULIC COUPLING 4" ONE BOLT	71910-002502	11
11	VICTAULIC COUPLING 6" TWO BOLT	71910-002503	4
12	Control stand + controller + Aquative bracket		1
13	1" CONTROL KIT FOR MEDIA FILTER - NPT	37090-009610	1
14	L.P. Check point (part of control kit)		1
15	BARAK PLASTIC BASE 2 GD-010(NPT)	70561-001500	1
16	SUPPORT LEG 6"-200MM	71910-001909	3
17	SUPPORT LEG 4"-1400MM	71910-001952	1





SAP DESCRIPTION	:				ETA!	
MTL SNG 480306 S				V . 14	ETA	r 1 M
SKU No.				THE INFORM DRAWING IS	ATION CONTA THE SOLE PRO	INED IN THIS
Maximum Flow Rate	: 1122 GPM			NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED		
Recommended Flow Rate: 616 GPM				Designed By		
Inlet Pressure:	115 PSI			Drawn By	KEREM	25/12/2019
Sheet Size:	Scale:			Checked By		
A4	1:40	to high Pressure	TO LOW PRESSURE	QA		
		D.P /	D.P	Sheet: 3	^{Of:} 3	Rev