



UNIRAM™ HCNL

INTEGRAL PRESSURE-COMPENSATING,
CONTINUOUSLY SELF-CLEANING, ANTI-SIPHON
AND HIGH ANTI-DRAIN MECHANISM DRIPPER



16009 - 16010 - 16012 - 17012 - 20010 - 20012 - 23010

TECHNICAL INFORMATION

- Pressure-compensating range: 1.5-4.0 bar.
- Anti-Siphon and higher pressure range of the Anti-drain mechanism.
- Largest filter in each dripper. Recommended filtration: 130 micron / 120 mesh.
Filtration method is to be selected based on the kind and concentration of the dirt particles existing in the water.
Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclone is to be installed before the main filter.
When sand/ silt/ clay solids exceed 100 ppm, pre treatment will be applied according to Netafim™ expert team's instructions.
- Double TurboNet™ labyrinth with large water passage.
- To be "welded" into thick-walled dripperlines (0.90, 1.00, 1.20 mm).
- Injected dripper, very low CV.
- Injected silicon diaphragm.
- High UV resistant. Resistant to standard nutrients used in agricultural.
- UniRam™ dripperlines meet ISO 9261 Standards with production certified by the Israel Standards Institute (SII).

DRIPPERS TECHNICAL DATA

FLOW RATE* (L/H)	WORKING PRESSURE RANGE (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXPONENT * X	RECOMMENDED FILTRATION (MICRON)/(MESH)	SHUT OFF PRESSURE (BAR)
0.85	1.5 – 4.0	0.70 x 0.65 x 40	110	0.85	0	130/120	0.25
1.25	1.5 – 4.0	0.83 x 0.74 x 40	130	1.25	0	130/120	0.25
2.00	1.5 – 4.0	1.07 x 0.79 x 40	130	2.00	0	130/120	0.25
2.90	1.5 – 4.0	1.26 x 0.95 x 40	130	2.90	0	130/120	0.25
4.40	1.5 – 4.0	1.59 x 1.10 x 40	150	4.40	0	130/120	0.25

* Within working pressure range

DRIPPERLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
16009	14.2	0.9	16.0	3.0	3.9	1.3
16010	14.2	1.0	16.2	3.5	4.6	1.3
16012	14.2	1.2	16.6	4.0	5.2	1.3
17012	14.6	1.2	17.0	4.0	5.2	1.1
20010	17.5	1.0	19.5	3.5	4.6	0.4
20012	17.5	1.2	19.9	4.0	5.2	0.4
23010	20.8	1.0	22.8	3.0	3.5	0.3

DRIPPERLINES PACKAGE DATA (ON BUNDLED COILS)

MODEL	WALL THICKNESS (MM)	COIL LENGTH (M)	DISTANCE BETWEEN DRIPPERS (M)	AVERAGE* COIL WEIGHT (KG)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
16009	0.9	500	0.15 to 1.00	20.3	330	165000
16010	1.0	500	0.15 to 1.00	22.1	330	165000
16012	1.2	400	0.15 to 1.00	21.2	352	140800
17012	1.2	400	0.15 to 1.00	22.4	352	140800
20010	1.0	300	0.15 to 1.00	17.4	330	99000
20012	1.2	300	0.15 to 1.00	20.2	330	99000
23010**	1.0	200	0.15 to 0.25	14.7	480	96000
		300	0.30 to 1.00	20.7		144000

*According to drippers spacing

**Package only on carton/plastic coils

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 16009/16010/16012 • ID 14.2 MM • KD 1.3 • FLOW RATE 0.85 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
UPHILL 2%	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	2.0	75	101	123	141	155	167	178	186	194
	2.5	99	137	171	200	225	247	267	285	301
	3.0	116	162	203	240	272	302	329	353	375
	3.5	129	182	229	271	310	344	377	407	434
	4.0	140	198	250	298	341	380	417	451	483
FLAT TERRAIN	2.0	84	121	155	187	217	246	274	301	326
	2.5	107	153	197	238	277	314	349	383	415
	3.0	122	176	226	274	319	361	402	441	479
	3.5	135	194	250	303	352	399	444	488	530
	4.0	146	210	270	327	380	431	480	527	573
DOWNHILL 2%	2.0	94	141	188	236	283	330	378	425	472
	2.5	114	170	224	277	330	382	434	485	536
	3.0	129	191	250	309	365	421	477	532	586
	3.5	141	207	272	334	395	454	514	572	628
	4.0	151	222	290	356	421	483	545	606	665

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 16009/16010/16012 • ID 14.2 MM • KD 1.3 • FLOW RATE 1.25 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
UPHILL 2%	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	2.0	60	82	101	117	131	143	154	162	170
	2.5	78	110	137	162	184	204	222	238	253
	3.0	91	128	162	192	220	245	268	290	310
	3.5	101	143	181	216	248	277	305	330	354
	4.0	109	156	198	236	272	305	335	365	391
FLAT TERRAIN	2.0	65	94	121	146	169	192	214	234	254
	2.5	83	119	153	185	215	244	272	298	324
	3.0	95	137	176	213	248	281	313	344	373
	3.5	105	151	194	235	274	311	346	380	413
	4.0	113	163	210	254	296	335	374	410	446
DOWNHILL 2%	2.0	71	106	140	175	209	243	277	311	344
	2.5	87	129	169	209	247	286	323	360	397
	3.0	99	146	190	234	276	318	358	399	438
	3.5	108	159	207	254	300	344	388	430	472
	4.0	116	170	222	272	320	367	413	458	502

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 16009/16010/16012 • ID 14.2 MM • KD 1.3 • FLOW RATE 2.0 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	45	63	78	92	104	114	124	133	141
	2.5	58	82	104	124	142	158	173	187	200
	3.0	67	96	122	146	167	188	206	224	240
	3.5	75	107	136	163	188	211	233	253	272
	4.0	81	116	148	177	205	230	254	277	299
FLAT TERRAIN	2.0	48	69	89	107	125	141	158	173	187
	2.5	61	88	112	136	158	180	200	220	239
	3.0	70	101	130	157	182	207	230	253	275
	3.5	77	111	143	173	202	229	255	280	304
	4.0	83	120	154	187	218	247	275	302	329
DOWNHILL 2%	2.0	51	76	100	123	146	169	192	214	236
	2.5	63	93	121	149	176	202	228	254	279
	3.0	72	105	137	168	198	227	255	284	311
	3.5	79	115	150	184	215	247	278	308	337
	4.0	85	124	161	197	231	264	297	329	359

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 16009/16010/16012 • ID 14.2 MM • KD 1.3 • FLOW RATE 2.90 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	36	50	63	75	85	95	103	111	118
	2.5	46	65	83	99	114	127	141	152	164
	3.0	53	76	97	116	134	151	166	181	195
	3.5	59	84	108	130	149	169	186	203	220
	4.0	64	92	117	141	163	184	203	222	240
FLAT TERRAIN	2.0	38	54	70	84	98	111	124	136	147
	2.5	48	69	88	107	125	141	158	173	188
	3.0	55	79	102	123	143	162	182	199	216
	3.5	60	87	112	136	158	180	200	221	239
	4.0	65	94	121	147	171	194	217	238	259
DOWNHILL 2%	2.0	40	58	76	94	111	128	145	161	178
	2.5	49	72	94	115	135	155	174	194	213
	3.0	56	82	106	130	153	175	197	218	238
	3.5	61	89	116	142	167	191	214	237	259
	4.0	66	96	125	153	179	204	230	254	277

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 16009/16010/16012 • ID 14.2 MM • KD 1.3 • FLOW RATE 4.40 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	UPHILL 2%	2.0	28	39	49	59	67	75	82	89
2.5		35	50	64	77	89	100	110	120	129
3.0		41	58	74	90	104	117	130	141	153
3.5		45	65	83	100	116	131	145	158	171
4.0		49	70	90	108	125	142	158	173	187
FLAT TERRAIN	2.0	29	41	53	64	75	85	94	104	113
	2.5	36	52	67	82	95	108	120	132	144
	3.0	41	60	77	94	109	124	138	152	165
	3.5	46	66	85	104	121	137	153	168	183
	4.0	49	71	92	112	130	148	165	182	198
DOWNHILL 2%	2.0	30	44	57	70	83	95	107	119	130
	2.5	37	54	70	86	101	116	130	144	158
	3.0	42	62	80	98	115	131	147	163	178
	3.5	46	68	88	107	125	144	161	178	194
	4.0	50	73	94	115	135	154	173	191	208

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 17012 • ID 14.6 MM • KD 1.1 • FLOW RATE 0.85 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	UPHILL 2%	2.0	80	108	130	148	162	174	184	192
2.5		107	147	182	212	237	260	280	298	313
3.0		125	174	217	255	289	319	346	371	393
3.5		139	195	245	289	329	365	398	428	456
4.0		151	213	268	317	362	403	441	476	508
FLAT TERRAIN	2.0	91	131	167	201	233	263	292	320	347
	2.5	116	166	212	256	296	335	373	409	443
	3.0	133	191	244	294	341	386	430	471	510
	3.5	146	210	270	325	377	427	475	521	565
	4.0	158	227	291	351	408	462	514	563	611
DOWNHILL 2%	2.0	103	154	205	257	308	359	410	462	513
	2.5	125	185	243	301	358	414	470	525	580
	3.0	141	207	271	334	395	456	516	574	633
	3.5	154	225	294	362	427	491	554	616	677
	4.0	165	241	314	386	454	522	587	653	716

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 17012 • ID 14.6 MM • KD 1.1 • FLOW RATE 1.25 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
TERRAIN	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	UPHILL 2%	2.0	64	88	107	124	137	149	160	168
2.5		84	118	146	172	194	215	233	249	265
3.0		98	138	173	205	233	260	283	305	326
3.5		109	154	194	231	264	295	323	349	373
4.0		118	168	212	253	290	324	356	385	413
FLAT TERRAIN	2.0	71	101	130	157	181	205	228	249	270
	2.5	90	129	165	199	231	261	290	318	345
	3.0	103	148	190	229	266	301	334	366	398
	3.5	114	163	209	253	293	333	370	406	440
	4.0	123	176	226	273	317	360	400	438	476
DOWNHILL 2%	2.0	78	116	153	190	227	264	300	337	372
	2.5	95	140	184	226	268	309	350	389	429
	3.0	108	158	206	253	299	343	386	429	472
	3.5	118	173	224	275	324	371	418	464	508
	4.0	127	185	240	294	346	396	445	492	540

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 17012 • ID 14.6 MM • KD 1.1 • FLOW RATE 2.00 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
TERRAIN	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	UPHILL 2%	2.0	48	67	83	97	110	120	130	139
2.5		63	89	111	132	150	167	182	197	210
3.0		73	103	131	156	178	200	218	237	254
3.5		81	115	146	174	200	225	247	268	288
4.0		88	125	159	190	218	246	270	294	317
FLAT TERRAIN	2.0	52	75	96	115	134	151	168	185	200
	2.5	66	95	121	147	170	193	214	235	255
	3.0	76	109	140	169	196	222	246	271	294
	3.5	83	120	154	186	217	245	273	299	325
	4.0	90	130	166	201	234	265	295	323	351
DOWNHILL 2%	2.0	56	82	108	134	158	183	207	231	256
	2.5	69	101	132	161	190	218	246	274	300
	3.0	78	114	148	182	214	245	275	305	334
	3.5	86	125	162	198	233	266	298	330	362
	4.0	92	134	174	212	249	284	319	353	386

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 17012 • ID 14.6 MM • KD 1.1 • FLOW RATE 2.90 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	39	54	67	80	90	100	109	117	124
	2.5	50	71	89	106	121	136	149	161	173
	3.0	58	82	104	124	143	160	177	192	206
	3.5	64	91	116	139	160	180	198	216	233
	4.0	69	99	126	151	174	196	217	237	255
FLAT TERRAIN	2.0	41	59	75	91	105	119	132	145	157
	2.5	52	74	95	115	134	151	168	185	200
	3.0	59	85	110	132	154	174	194	212	231
	3.5	65	94	121	146	170	193	214	235	255
	4.0	70	101	130	158	184	208	232	255	276
DOWNHILL 2%	2.0	43	63	83	102	121	139	157	175	192
	2.5	53	78	102	124	146	167	188	209	229
	3.0	61	89	115	141	165	188	211	234	256
	3.5	67	97	126	154	180	206	230	255	278
	4.0	72	104	135	165	193	221	246	273	298

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 17012 • ID 14.6 MM • KD 1.1 • FLOW RATE 4.40 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	30	42	53	63	71	80	87	95	101
	2.5	38	54	69	83	95	106	118	128	137
	3.0	44	63	80	96	111	125	138	150	162
	3.5	49	70	89	107	124	139	154	168	182
	4.0	53	76	97	116	134	152	168	184	199
FLAT TERRAIN	2.0	31	45	57	69	80	91	101	111	120
	2.5	39	56	72	88	102	116	129	141	153
	3.0	45	65	83	101	118	133	148	163	176
	3.5	50	72	92	112	130	147	164	180	195
	4.0	54	77	99	120	140	159	177	194	211
DOWNHILL 2%	2.0	32	47	62	76	89	102	115	128	140
	2.5	40	59	76	93	109	125	140	155	170
	3.0	46	67	86	106	124	141	158	175	191
	3.5	50	73	95	116	136	155	173	191	208
	4.0	54	79	102	124	145	166	186	204	223

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 20010/20012 • ID 17.5 MM • KD 0.4 • FLOW RATE 0.85 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	118	150	172	188	199	209	215	221	225
	2.5	164	215	256	289	315	337	355	372	385
	3.0	195	260	314	359	396	428	457	482	504
	3.5	219	296	359	413	460	501	538	570	599
	4.0	239	325	397	459	513	561	605	644	679
FLAT TERRAIN	2.0	148	206	258	306	350	392	432	470	506
	2.5	188	262	329	391	448	501	552	601	648
	3.0	216	302	379	451	517	579	638	694	748
	3.5	239	334	420	499	572	641	706	769	829
	4.0	258	361	454	539	619	694	765	833	898
DOWNHILL 2%	2.0	178	265	351	437	521	607	691	776	860
	2.5	212	310	405	498	589	679	769	857	945
	3.0	238	344	447	546	643	738	831	923	1015
	3.5	258	373	481	586	688	787	885	980	1075
	4.0	276	397	512	621	727	831	932	1031	1129

Minimum considered pressure 1.5 bar Max. working pressure according the dripperline wall thickness definition
 Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 20010/20012 • ID 17.5 MM • KD 0.4 • FLOW RATE 1.25 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	97	126	147	164	177	188	196	203	209
	2.5	131	176	211	242	266	288	307	324	338
	3.0	155	210	255	295	329	358	386	410	431
	3.5	174	236	290	336	377	414	447	477	504
	4.0	189	259	319	371	418	460	498	533	566
FLAT TERRAIN	2.0	115	160	201	239	273	306	337	366	395
	2.5	146	204	256	304	349	391	431	469	506
	3.0	168	235	295	351	403	452	498	542	584
	3.5	185	260	327	389	446	500	551	600	647
	4.0	200	281	353	420	482	541	597	650	701
DOWNHILL 2%	2.0	133	196	258	318	378	438	497	555	614
	2.5	161	233	302	370	435	500	563	626	688
	3.0	181	261	336	409	479	548	615	681	747
	3.5	197	283	364	442	516	589	659	729	797
	4.0	211	303	388	470	548	624	698	770	841

Minimum considered pressure 1.5 bar Max. working pressure according the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 20010/20012 • ID 17.5 MM • KD 0.4 • FLOW RATE 2.00 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	75	99	118	135	148	159	168	176	183
	2.5	99	135	164	190	212	232	250	266	280
	3.0	117	159	196	228	257	282	306	327	347
	3.5	130	179	221	258	292	322	350	375	399
	4.0	141	195	242	283	320	355	386	416	443
FLAT TERRAIN	2.0	85	118	148	176	202	226	249	271	292
	2.5	107	150	189	225	257	289	318	347	374
	3.0	124	173	218	259	297	333	368	401	432
	3.5	136	191	241	287	329	369	407	444	478
	4.0	147	207	260	310	356	400	441	480	518
DOWNHILL 2%	2.0	94	137	179	220	259	298	337	375	413
	2.5	115	166	214	260	305	348	390	433	474
	3.0	131	187	240	291	339	386	432	477	521
	3.5	143	204	261	316	367	418	466	514	560
	4.0	153	219	279	337	392	445	496	546	595

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 20010/20012 • ID 17.5 MM • KD 0.4 • FLOW RATE 2.90 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	60	81	98	113	125	135	145	153	160
	2.5	79	108	133	155	175	192	207	222	235
	3.0	93	128	158	185	209	230	250	269	287
	3.5	103	143	177	208	236	261	285	307	327
	4.0	112	155	193	227	258	287	314	338	361
FLAT TERRAIN	2.0	66	93	116	139	159	178	196	213	230
	2.5	84	118	148	177	203	228	251	274	295
	3.0	97	136	171	204	234	263	290	315	340
	3.5	107	150	189	226	259	291	321	349	377
	4.0	116	162	204	244	280	314	347	378	408
DOWNHILL 2%	2.0	72	105	136	166	194	223	251	278	306
	2.5	89	128	164	199	232	264	296	327	357
	3.0	101	144	185	223	260	295	330	363	395
	3.5	111	158	202	243	283	321	357	392	428
	4.0	119	170	216	261	302	342	381	419	455

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 20010/20012 • ID 17.5 MM • KD 0.4 • FLOW RATE 4.40 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	47	64	78	91	101	111	119	127	134
	2.5	61	84	104	123	139	153	166	179	190
	3.0	71	99	123	145	164	182	198	214	229
	3.5	79	110	137	162	184	205	224	242	259
	4.0	86	119	149	177	201	224	246	266	285
FLAT TERRAIN	2.0	51	71	89	106	121	137	150	164	176
	2.5	64	90	113	135	155	174	192	209	225
	3.0	74	104	131	156	179	201	222	241	260
	3.5	81	115	144	172	198	222	245	267	288
	4.0	88	124	156	186	214	240	266	289	312
DOWNHILL 2%	2.0	54	78	100	122	142	162	182	202	221
	2.5	67	96	122	148	172	195	218	240	262
	3.0	76	109	138	167	194	220	245	269	293
	3.5	84	119	152	183	212	239	266	293	318
	4.0	90	128	163	196	227	257	286	313	340

Minimum considered pressure 1.5 bar

Max. working pressure according to the dripperline wall thickness definition

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 23010 • ID 20.8 MM • KD 0.3 • FLOW RATE 0.85 L/H

	DISTANCE BETWEEN DRIPPERS (METER)									
	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
UPHILL 2%	2.0	148	180	200	213	221	228	232	235	238
	2.5	212	272	316	349	374	393	409	421	432
	3.0	256	335	396	446	485	518	545	568	588
FLAT TERRAIN	2.0	202	281	351	416	475	531	585	635	685
	2.5	257	358	448	531	607	680	748	814	877
	3.0	296	412	516	612	701	785	865	941	1013
DOWNHILL 2%	2.0	258	389	521	654	786	918	1051	1184	1317
	2.5	303	447	588	729	867	1005	1142	1279	1415
	3.0	336	491	641	789	933	1077	1218	1359	1498

Minimum considered pressure 1.5 bar

Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 23010 • ID 20.8 MM • KD 0.3 • FLOW RATE 1.25 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
UPHILL 2%	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	2.0	124	155	177	193	204	212	218	224	228
	2.5	173	226	267	300	326	348	366	382	394
	3.0	206	274	328	374	412	445	474	498	520
FLAT TERRAIN	2.0	157	218	273	324	371	414	457	496	534
	2.5	200	278	349	414	473	531	584	635	684
	3.0	230	320	402	477	547	613	674	734	791
DOWNHILL 2%	2.0	191	285	378	470	562	655	746	838	929
	2.5	227	332	434	534	632	729	826	922	1016
	3.0	254	368	478	585	688	790	890	990	1088

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 23010 • ID 20.8 MM • KD 0.3 • FLOW RATE 2.00 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
UPHILL 2%	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	2.0	97	126	148	164	177	188	196	203	209
	2.5	132	176	212	242	267	289	308	324	339
	3.0	156	211	256	295	329	359	386	410	431
FLAT TERRAIN	2.0	116	161	202	239	274	307	338	367	395
	2.5	147	205	257	305	350	392	432	470	506
	3.0	169	236	296	352	404	452	498	543	585
DOWNHILL 2%	2.0	134	197	259	320	379	439	498	556	615
	2.5	162	234	304	371	437	501	564	627	689
	3.0	182	262	338	411	481	550	617	683	748

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 23010 • ID 20.8 MM • KD 0.3 • FLOW RATE 2.90 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
UPHILL 2%	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	2.0	80	105	124	141	154	165	174	183	189
	2.5	106	143	174	201	223	244	262	277	292
	3.0	125	170	208	242	271	298	322	344	364
FLAT TERRAIN	2.0	91	127	158	188	215	242	266	289	312
	2.5	115	161	202	240	275	309	340	370	399
	3.0	133	185	233	277	317	356	393	428	461
DOWNHILL 2%	2.0	102	149	194	238	281	324	366	408	449
	2.5	124	179	231	281	329	376	422	468	512
	3.0	141	201	258	313	365	417	466	514	562

Minimum considered pressure 1.5 bar

MAX. LATERAL LENGTH (METER) AT DIFFERENT INLET PRESSURE AND DIFFERENT SLOPES

UNIRAM™ HCNL 23010 • ID 20.8 MM • KD 0.3 • FLOW RATE 4.40 L/H

		DISTANCE BETWEEN DRIPPERS (METER)								
UPHILL 2%	INLET PRESSURE (BAR)	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
	2.0	63	84	101	116	128	139	148	157	164
	2.5	83	113	138	160	180	197	214	228	242
	3.0	96	132	163	191	215	238	258	277	295
FLAT TERRAIN	2.0	69	97	121	144	165	185	203	221	239
	2.5	88	123	154	184	211	236	260	284	305
	3.0	101	141	178	212	243	272	300	327	352
DOWNHILL 2%	2.0	76	110	142	173	203	233	262	291	320
	2.5	93	133	171	207	242	275	308	340	372
	3.0	106	151	193	233	271	307	343	378	412

Minimum considered pressure 1.5 bar